



Ref. Certif. No.

CN55044

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Air circuit breaker
Name and address of the applicant	Zhejiang CHINT Electrics Co., Ltd. No.1, CHINT Road, CHINT Industrial Zone, North Baixiang Town, Yueqing City, Zhejiang Province, P.R.China
Name and address of the manufacturer	Zhejiang CHINT Electrics Co., Ltd. No.1, CHINT Road, CHINT Industrial Zone, North Baixiang Town, Yueqing City, Zhejiang Province, P.R.China
Name and address of the factory	Wenzhou CHINT Electrics Technology Co., Ltd. No.1318, Binhai No.2 Avenue, Economic and Technical Development Zone, Wenzhou City, Zhejiang Province, P.R.China
<i>Note: When more than one factory, please report on page 2</i>	
Ratings and principal characteristics	See the Appendix
Trademark / Brand (if any)	CHINT
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	NXA25N,NXA25H,NXA25N/4,NXA25H/4,NXA25N/NE,NXA25H/NE,NXA25N/4NE,NXA25H/4NE,NXAF25N,NXAF25H,NXAF25N/4,NXAF25H/4;
Additional information (if necessary may also be reported on page 2)	
A sample of the product was tested and found to be in conformity with	IEC 60947-2:2016/AMD1:2019;IEC 60947-2:2016(5th Edition)
As shown in the Test Report Ref. No. which forms part of this Certificate	00901-CB2021CQC-099019

This CB Test Certificate is issued by the National Certification Body

CHINA QUALITY CERTIFICATION CENTRE

Section 9, No. 188 Nansihuan Xilu, Beijing 100070 P. R. China
Tel: +86-10-83886666 Fax: +86-10-83886282
website: http://www.cqc.com.cn



谢肇旭

Signature: Xie ZhaoXu

Date: Oct.21,2021

CB 0064527

NXA25N,NXA25H,NXA25N/4,NXA25H/4,NXA25N/NE,NXA25H/NE,NXA25N/4NE,NXA25H/4NE,NXAF25N,NXAF25H,NXAF25N/4,NXAF25H/4;

Uimp:12kV;

Ui: 1000V;

Ue: AC380V/AC400V/AC415V, AC440V/AC525V/AC690V;

In:630A,800A,1000A,1250A,1600A,2000A,2500A;

Over-current release: electronic;

NXA25N,NXA25N/4,NXA25N/NE,NXA25N/4NE,NXAF25N,NXAF25N/4:

Ics=80kA(AC380V/AC400V/AC415V), 50kA(AC440V/AC525V/AC690V);

Icu=80kA(AC380V/AC400V/AC415V), 50kA(AC440V/AC525V/AC690V);

Icw=55kA/1s(AC380V/AC400V/AC415V), 50kA/1s(AC440V/AC525V/AC690V);

NXA25H,NXA25H/4,NXA25H/NE,NXA25H/4NE,NXAF25H,NXAF25H/4:

Ics=85kA(AC380V/AC400V/AC415V),55kA(AC440V/AC525V/AC690V);

Icu=85kA(AC380V/AC400V/AC415V), 55kA(AC440V/AC525V/AC690V);

Icw=65kA/1s(AC380V/AC400V/AC415V), 55kA/1s(AC440V/AC525V/AC690V);

Selectivity category: B;

Pole: 3P, 4P;

Frequency :50Hz/60Hz;

Applicable for isolation;

IP20;

Auxiliary contact and alarm contact:

4NO4NC,6NO6NC;Ui: 415V;lth: 6A;

Ue/Ie: AC-15: AC415V/0.75A, AC240V/1.3A;DC-13: DC220V/0.27A, DC110V/0.55A;


Page 1 of 1

Additional information (if necessary)

Date:

Oct.21,2021

Signature:



Xie ZhaoXu